

RUNner



For sliding gates up to 8 m travel length and 600 kg weight



Safety

- High safety due to fully automatic force memory
- Automatic detection of safety edges (8,2 kOhm or OSE) and light barriers (2 and 4 wire)
- Pre-warning function and dead-man operation
- Frequency-modulated safe SOMMER Radio Control System

Easy to install

- Left or right door operation adjustable via selection switch; no rewiring of motor and end switch is necessary
- Automatic / semi automatic closing is possible from the end position and partial-opening position; partial opening position is adjustable



Flexibility

- Energy-saving toroidal core transformer is environmentally-friendly and saves money
- Connection option for battery pack¹⁾ provides buffer in the event of a power failure

TECHNICAL DATA

Temperature range	-30 °C to +50 °C
Nominal voltage	AC 220 - 240 V
Torque	max. 20 Nm
Nominal frequency	50/60 Hz
IP code	IP54

RUNner single operator

3520V000
incl. 1 x sliding gate operator, control unit STB-1, integrated radio receiver (FM 868.8 MHz)

RUNner complete set

3521V000
1 x sliding gate operator, control unit STB-1, 4 m steel rack bonded with plastic, integrated radio receiver (FM 868.8 MHz), 4-command transmitter (# 4020V000)

¹⁾ available as accessory

Last updated: 02/2015. Literal errors, errors and technical changes excepted.

